

5 **Amendments in the Claims:** (struck-through parts deleted and underlined parts added)

1. (currently amended) A wheel lock device for selectively locking on a wheel rim, said device comprising:

an elongated member having a first end and a second end, said elongated member having a first side and a second side positioned opposite of each other,
10 said first side having a plurality of teeth positioned thereon;

a first arm being attached to said first side and extending away therefrom, said first arm being orientated generally perpendicular to said elongated member, said first arm being positioned adjacent to said first end, a foot being attached to a free end of said first arm, said foot extending in a same
15 direction as said first end;

a sleeve being positioned on said elongated member and being selectively movable between said first end and said second end, said sleeve having an upper wall, a bottom wall, an inner wall and an outer wall, said inner wall being positioned adjacent to said first side, said inner wall of said sleeve
20 having an inner surface having a plurality of teeth thereon;

an urging member being mounted in said outer wall for selectively biasing said outer wall away from said elongated member;

a second arm being attached to an outer surface of said inner wall and extending in a same direction as said first arm, a foot being attached to a free end of said second arm, said foot extending in a same direction as second end;
25 and

~~wherein said first and second legs may be selectively extended into openings in the wheel rim and said second leg moved away from said first leg such that said first and second legs engage the rim~~

30 each of said first and second arms being selectively extendable into openings in the wheel rim and said second arm being selectively movable away from said first arm such that said first and second arms releasably engage the rim.

35 Claim 2 (cancelled)

5

3. (currently amended) The wheel lock device of claim 2 1, wherein said urging member being positionable in an extended position or a retracted position, said teeth on said first side engaging said teeth on said inner surface of said inner wall when said urging member is in said extended position.

10

4. (original) The wheel lock device of claim 3, further including a lock being mechanically coupled to said urging member for selectively locking said urging member in said extended position.

15

5. (original) The wheel lock device of claim 3, said second side having an elongated slot therein extending between said first and second ends, a guide being attached to said outer wall, said guide extending into said slot

20

6. (original) The wheel lock device of claim 3, further including a weight being attached to said second end of said elongated member.

7. (currently amended) A wheel lock device for selectively locking on a wheel rim, said device comprising:

25

an elongated member having a first end and a second end, said elongated member having a first side and a second side positioned opposite of each other, said first side having a plurality of teeth positioned thereon, said second side having an elongated slot therein extending between said first and second ends;

30

a first arm being attached to said first side and extending away therefrom, said first arm being orientated generally perpendicular to said elongated member, said first arm being positioned adjacent to said first end, a foot being attached to a free end of said first arm, said foot extending in a same direction as said first end;

35

a sleeve being positioned on said elongated member and being selectively movable between said first end and said second end, said sleeve having an

5 upper wall, a bottom wall, an inner wall and an outer wall, said inner wall
being positioned adjacent to said first side, said inner wall having an inner
surface having a plurality of teeth thereon;
an urging member being mounted in said outer wall for selectively biasing said
outer wall away from said elongated member, said urging member being
10 positionable in an extended position or a retracted position, a lock being
mechanically coupled to said urging member for selectively locking said
urging member in said extended position, a guide being attached to said
outer wall, said guide extending into said slot, said teeth on said first side
engaging said teeth on said inner surface of said inner wall when said
15 urging member is in said extended position;
a second arm being attached to an outer surface of said inner wall and extending
in a same direction as said first arm, a foot being attached to a free end of
said second arm, said foot extending in a same direction as second end;
a weight being attached to said second end of said elongated member; and
20 ~~wherein said first and second legs may be selectively extended into openings in
the wheel rim and said second leg moved away from said first leg such
that said first and second legs engage the rim~~
each of said first and second arms being selectively extendable into openings in
the wheel rim and said second arm being selectively movable away from
said first arm such that said first and second arms releasably engage the
25 rim.